
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☐ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☐ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☒ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Lilly Industries, Inc.
Product Name: Goof Off, Non-Aerosol

2400, 2401, 2405, 2408, 2409, 2410, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2423, 2424, 2425, 2428, 2429, 2430, 2431, 2432, 2448, 2450, 2455, 2480, 2481, 2490, 2494, 2499

MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION: 16MAY00
MANUFACTURER'S NAME: SPECIALTY BUSINESS UNIT
MANUFACTURER'S ADDRESS: LILLY INDUSTRIES, INC.
4999 36TH STREET S.E.
GRAND RAPIDS, MI 49518
EMERGENCY (CHEM-TEL) PHONE NO.: 1-800-255-3924
EMERGENCY/INFORMATION PHONE NO.: (616) 940-2900

SECTION I: PRODUCT INFORMATION

PRODUCT NAME: Goof Off, Non-Aerosol
MANUFACTURERS CODE IDENTIFICATION: 2400, 2401, 2405, 2408, 2409, 2410, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2423, 2424, 2425, 2428, 2429, 2430, 2431, 2432, 2448, 2450, 2455, 2480, 2481, 2490, 2494, 2499
PRODUCT CLASS: Liquid Cleaner

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	CAS Number	BY WGT.	Occupational Exposure Limits				Vapor Pres.
			PEL	TLV	UNITS	LEL	
+ Xylene	1330-20-7	90 - 95	100	100	ppm	1.00	6.60
+ Diethylene glycol monomethyl ether	111-77-3	1 - 5	---	---	---	ND	ND

+ SARA III - Section 313 Toxic Chemical

SECTION III: PHYSICAL DATA

EVAPORATION RATE: ☐ FASTER ☒ SLOWER THAN ETHER
VAPOR DENSITY: ☒ HEAVIER ☐ LIGHTER THAN AIR
BOILING RANGE: 147°F Initial Boiling Point C.A.R.B. VOC:
PERCENT VOLATILE: 99 POUNDS PER GALLON: 7.3 SPECIFIC GRAVITY .87 typical

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASS: IB Flammable Liquid
LOWER EXPLOSIVE LIMIT: See Section II
HMS RATING:
Health 2 Flammability 3 Reactivity 0
FLASH POINT: 50°F
EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide. Water is not suitable as an extinguishing media, but may be used to cool nearby containers.

The Information Contained Herein is Based on Data Believed to be Reliable by
Lilly Industries, Inc.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Pressure may develop in closed containers if overheated. Empty containers with residual amounts of material are still potentially flammable. Flammable liquids may release vapors which can form a flammable mixture with air at or above the flashpoint.

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighters should wear normal protective equipment and positive pressure breathing apparatus.

SECTION V: HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: May cause eye irritation, redness, tearing, blurred vision. Skin contact may cause irritation, redness, dermatitis and defatting with prolonged or repeated exposure. Excessive inhalation of vapors may cause respiratory irritation, dizziness, nausea, asphyxiation. Ingestion may cause gastrointestinal irritation, nausea, vomiting, diarrhea. Aspiration of material into lungs may cause chemical pneumonitis, which can be fatal. Prolonged or repeated occupational overexposure to solvents may cause permanent brain and nervous system damage. Intentional misuse by deliberate concentration and inhalation of contents may be harmful or fatal.

EMERGENCY FIRST AID PROCEDURES: For eye contact, flush with running water for 15 minutes, holding lid open to expose surface of eye, contact physician. For skin, remove contaminated clothing and shoes, wash with mild soap and water. If affected by vapors or spray mists, remove to fresh air at once. Apply artificial respiration if necessary, contact physician immediately. If swallowed, do not induce vomiting, get medical attention immediately.

SECTION VI: REACTIVITY DATA

STABILITY: ☐ UNSTABLE ☒ STABLE

CONDITIONS TO AVOID: Exposure to high heat, sparks, open flame, or other sources of ignition.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers like chlorine.

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes, smoke, CO_x, oxides of other organic elements.

HAZARDOUS POLYMERIZATION: ☐ MAY OCCUR ☒ WILL NOT OCCUR

CONDITIONS TO AVOID: Avoid high temperatures, direct heat

SECTION VII: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove ignition sources. Dike and take up with absorbent material. Ensure adequate ventilation, avoid buildup of vapors.

WASTE DISPOSAL METHOD: Dispose in accordance with all applicable regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below exposure guidelines. When respiratory protection is required, use appropriate, properly fitted NIOSH/MSHA approved equipment.

2400, 2401, 2405, 2408, 2409, 2410, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2423, 2424, 2425, 2428, 2429, 2430, 2431, 2432, 2448, 2450, 2455, 2480, 2481, 2490, 2494, 2499

2400

VENTILATION: Control airborne concentrations below exposure guidelines. Local exhaust ventilation may be necessary.

PROTECTIVE GLOVES: Use chemical resistant gloves when necessary to protect from personal exposure.

EYE PROTECTION: Face shield or safety glasses are recommended.

OTHER PROTECTIVE EQUIPMENT: Other protective clothing should be used as necessary to protect from personal exposure. Ground all containers when transferring material.

SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers closed when not in use. Do not use or store near open flame or strong oxidizers.

OTHER PRECAUTIONS: Avoid breathing vapors or spray mists. Avoid prolonged or repeated personal contact. Wash thoroughly after use

DOT INFORMATION

UN Number	UN1307
Classification	3
Proper Shipping Name	Xylene solution
Packing Group	II
Exceptions	49CFR §173.150(b) & (c) allow for the use of the "ORM-D Consumer Commodity" classification for domestic ground shipment of packages <0.3 gallons net each.

KEEP OUT OF REACH OF CHILDREN

Creation Date: 04-28-97
Revision Date: 16MAY00
Revision Number: 4.0